

A WIDE RANGE OF CHEMICALS FOR A/C

MULTI-PURPOSE DYE

Art. No. 892.764040 (Oil Based)

Used for engine oil, transmissions, hydraulics, power steering, gasoline and diesel fuel

Includes:

6 dye bottles of 1 oz (30 ml) and 6 dye-installed stickers

Note: Not D.O.T. approved for brakes.



PAG OIL with UV dye

Art. No. 892.764425 (Viscosity 46) / 426 (100) / 024 (150)

Premium Synthetic Refrigerant Lubricant for R12 to R134a Systems
Approved O.E.M. Technology (Polyalkylene Glycol)

Contains:

- Conditioners, inhibitors and anti-wear agents for superior lubricity and compressor protection
- UV Dye for leak detector
- Specially formulated for O.E. and Aftermarket Air Conditioning Systems using R-134a refrigerant



ESTER OIL with UV dye

Art. No. 890.82908 (8oz) / Art. No. 890.82932 (32oz)

Premium Synthetic Refrigerant Lubricant for R12 to R134a Systems
Approved O.E.M. Technology

- Excellent anti-wear formulation, helps to extend compressor life
- Designed exclusively for retrofit applications
- Retro grade 100 equivalent to 500 viscosity
- Contains UV Dye for Leak Detector



A/C SUPER FLUSH

Art. No. 892.76402 - 4 l

- Ester-based flush is compatible with R-134a, R-22 and R-12 A/C lubricants.
- Absorbs and carries moisture from the system
- Will not react with copper, aluminum or brass
- Will not harm O-Rings, hoses, PAG, mineral or ester oil
- Non-hazardous and non-toxic, Non-flammable
- Biodegradable and environmentally friendly
- Aids in lubricating compressor.
- Use approximately 1 litre per application



NEW

A/C Performance Enhancer

Art. No. 893.13111



- Faster Cool-Down rates
- 3° to 9° Vent Reduction Temperature (on a normally operating system)
- Increases Cooling Capacity
- Reduces Cool-Down Time
- Cleans & Revitalizes R134a A/C Systems
- Reduces Compressor Wear
- Compatible with Pag, Ester, and Mineral Oils
- Will not harm A/C System Components or Equipment
- Ideal for both New Vehicles and Older Vehicles

Super A/C Leak Stop with u/v dye

Art. No. 892.764322

Stops small leaks in evaporator, condenser, hoses, O-rings and gaskets. Lubricates system and helps prevent leaks. Effective in R-134a and R-12 systems.

- Does not contain polymers. Will not harm A/C system components, reclamation or recovery machines
- 2 ounce bottle treats 1 vehicle
- Will not clog orifice tubes
- Installs easily using an oil injector



A/C Leak Sealant

Art. No. 892.764300 - 4 oz single application

25 % more contents than any other competitive product

Contains:

- U/V leak detector
- 2 oz ester oil charge
- Gasket conditioner
- 2 oz R134a refrigerant
- To be used with the 9" Reusable Charging Hose (Art. 892.764305)

Complete A/C system treatment, all in 1 step

- Premium Formulation stops leaks in automotive air conditioning system. Also treats o-rings and gaskets
- Compatible with mineral, ester and PAG oils





Quick-Fresh



Excellent for removing odours and returning a fresh air smell to vehicle air conditioning systems.

- Specially formulated to handle the problems associated with moisture accumulation
- The powerful fragrance and odour counteractant system does not just cover up offensive odours, but effectively eliminates them at the source
- Excellent for cars, trucks, RV's, boats, etc.
- Suitable to refreshen smoked-in vehicles, older cars, trucks
- Ideal for mildew and mould smell removal
- Pocket size

Description	Contents	Art. No.
Vanilla	4 oz.	893.76450
New Car Scent	4 oz.	893.76451
Linen scent	4 oz.	893.76452



Master A/C Retrofit Assortment

Art. No. 469.777

Characteristics: A complete universal A/C retrofit master kit.

Kit includes:

- 1 retrofit assortment: 18 components = 48 Pieces
- 1 A/C O-ring assortment: 18 sizes = 200 Pieces
- 1 bottle of ester oil (32 oz) containing UV dye

Advantage:

- Kit contains enough components to retrofit 8 to 10 vehicles
- Universal use ester oil is compatible with all POE, PAG and ester oils as well as with both R-12 and R-134 refrigerants
- Ester oil contains a UV dye which enables the technician to easily detect future A/C system leaks



Extendable U/V Pocket Light

Art. No. 764.1

- High powered (395 nm peak, 400 nm dominate) true U/V L.E.D.
- Rated for over 50,000 hours of use
- Perfect for close-up inspections
- Pocket sized, extendable (5.51 ~ 7.09 inches)
- Includes adjustable service mirror for those hard to see areas

Digital Thermometer

Art. No. 764.2

Precision temperature instrument

- 1 1/4" dial size
- 58 °F to 302 °F scale (-50 °C to 150 °C scale)
- Includes holder and clip
- Resolution: 0.1 °F or 0.1 °C
- 1 x 393 battery size, 1.5V
- Stem: stainless steel

Application:

Refrigeration, air conditioning, food service, industrial, laboratory, automotive



Universal High Side In-Line Filter

Art. No. 469.13128



- OEM tested and approved
- Protects against costly repeat compressor failure
- Single kit fits 5/16", 3/8" and 1/2" lines
- Can be used as a line splice or repair device for damaged orifice tube holders
- Quick and easy leak free installation

This System Contains Leak Sealant

Sealant Used

Date Installed / /

Leak Stop Identification Label

Art. No. 469.687.11

- Multi-use label advises of leak stop in A/C or other engine systems



VEHICLE AIR CONDITIONING SOLUTIONS

