

THE WÜRTH FINAL TOUCH

Würth Final Touch has been specially developed to correct any minor imperfection on automobile surfaces. Würth Final Touch is perfect for blending with **MAXI Plast** (Art. No. **892.60056** - 2kg) to improve flow-out and sanding.

Würth Final Touch

- * Pourable
- * Fast drying finishing putty
- * No pinholing
- * Resistant to staining
- * Easy sanding & feathering
- * Super smooth finish
- * Can be spread or brushed
- * Great for skim coats over MAXI Plast



Shop temperature: 21°C (70°F) or higher

Preparation: clean surface, remove dirt, oil and wax

Mixing: 2% of cream hardener (BPO), mix well

Application: use a spreader or a brush

Sanding: 10 minutes after gel time, use #180 grit sanding paper

Finish: use a quality primer such as the **Würth Self-Etch Primer** 12oz. (Art. No. **890.91700**)

NEW





A WIDE RANGE OF PUTTY FILLERS



Description	Content (kg)	Art. No.
Maxi Fine	2	892.60050

Maxi Fine

Polyglass technology reduces sanding time and paper clogging for an exceptional finished product.

- **Multi surface adhesion:** steel, aluminum, plastics, fiberglass, galvanized steels
- Reduced sanding pressure eliminates waving of today's thinner sheet metal body panels
- Sand dry or wet-on-wet after approximately 15 minutes
- Excellent with today's base clear technology
- Easy sanding
- High filling power, high elasticity
- White pigmentation
- No sinking on the top coat

Application:

Fine finishing application such as doors, hoods, trunks & fenders.



Description	Content (kg)	Art. No.
Maxi Plast	2	892.60056

Maxi Plast

Polyglass technology reduces sanding time and paper clogging for an exceptional finished product.

- **Multi surface adhesion:** steel, aluminum, plastics, fiberglass, galvanized steels
- Reduced sanding pressure eliminates waving of today's thinner sheet metal body panels
- Sand dry or wet-on-wet after approximately 15 minutes
- Excellent with today's base clear technology
- Easy sanding
- High filling power, high elasticity
- Beige pigmentation
- No sinking on the top coat

Application:

Especially useful on bumpers. High strength flexibility.



WÜRTH FINAL TOUCH: A REVOLUTION IN PUTTY FILLER

